

USER MANUAL



**We respect your choice for choosing AMP.
AMP company does everything possible
to ensure that our products meet your needs,
and quality match the best world standards.**

TWEETER
MASS
TW10

MADE IN PRC
specially for AMP™



AMPGROUP.RU

SPECIFICATIONS

Tweeter

Diameter	2" (50 mm)
Impedance	4Ω
Nom. power	10W
Max. power	20W
Sensitivity	90 dB
Frequency response	1500Hz – 20kHz
Magnet	Neodymium
Voice coil diameter	20 mm
Installation depth	16 mm
Installation diameter	41 mm



Акустика автомобильная, высокочастотный динамик

Диаметр	2" (50 мм)
Сопrotивление	4Ω
Мощность номинальная	10W
Мощность максимальная	20W
Чувствительность	90 dB
Диапазон частот	1500Hz – 20kHz
Магнит	Неодим
Звуковая катушка	20 мм
Монтажная глубина	16 мм
Монтажный диаметр	41 мм

Warranty period	12 months
Warranty lifetime	3 years
Warranty period of storage	5 years
The operating temperature	+5...+30°C
Transport and storage temperature	-20...+40°C

Гарантийный срок эксплуатации	12 месяцев
Гарантийный срок хранения	3 года
Гарантийный срок службы	5 лет
Рабочая температура окружающего воздуха	+5...+30°C
Температура транспортирования и хранения	-20...+40°C

CONNECTIONS

Crossover (TW)



Front speaker



Amplifier/Receiver



Your AMP product was developed and manufactured with high-quality materials and components which can be recycled and/or re-used. This symbol indicates that electrical and electronic equipment must be disposed of separately from normal garbage at the end of its operational lifetime. Please dispose of this product by bringing it to your local collection point or recycling centre for such equipment. This will help to protect the environment in which we all live.